


4CH MJPEG DVR

Features :

- Motion Detection recording
- Alarm Input / Output
- System auto detection (NTSC / PAL)
- Quad and each record image size
- Max. 120 images per second recording
- 400GB HDD support
- Removable HDD
- CF card backup
- TCP/IP network connection (option)
- Dynamic IP and DDNS support



YK-9810



YK-9811

Model No.	YK-9810	YK-9811
Video	Format	NTSC / EIA or PAL / CCIR
	Compression	MJPEG
	Input	4 CH, BNC
	Output	1 CH BNC, 1CH S-Video
	Loop-through	4 CH, BNC
Display	Resolution	720x480 (NTSC), 720x576 (PAL)
	Frame Rate	Max. 120 / 100 IPS (NTSC / PAL)
	Division	Single, Quad, Sequence
Recording	Resolution	Max. 640x272 (NTSC), 640x272 (PAL)
	Frame Rate	Max. 120 IPS@CIF / 100 IPS@CIF (NTSC / PAL)
	Quality	High / Normal / Low
HDD	Mode	Manual / Schedule / Alarm / Motion detection
	Basic Storage	1x3.5" IDE HDD (Max. 400GB)
Alarm	Input / Output	4 / 1
	Triggered Mode	Motion Detection, Video Loss, Sensor Input
	Action	Recording, Relay Output, Sound Alert
Network	Ethernet	10/100 BaseT Ethernet (RJ-45)
	Protocol	TCP/IP, PPPoE, DDNS, SMTP, ICMP, ARP
Post Alarm	0 ~ 60 sec	
Search Method	By Date, Time, Camera	
Backup Device	CF-Card, HDD, VCR	
Power Supply	AC100~240V 50/60 Hz, DC12V / 5A	
Weight	3 Kg (without HDD)	
Dimensions (WxHxD)	430x77x305 mm	
Operating Environment	30 ~ 80% RH, 5°C ~ 45°C (41°F ~ 113°F)	

■ IPS : Images Per Second